

Project :	Date :
Cat no. :	Type :
Notes :	Volts :

### Description:

The **NTALB-T60/T100** LED bars design provide a unique linear lighting solution combining style, performance and durability while reducing constructions and operating costs through installation time, energy savings and maintenance free application.

### Housing:

The **NTALB-T60/T100** are a high precision extruded anodized aluminum that can accept a LED linear source from normal to high power.

### Lens:

Precision fit extruded polycarbonate snap-in 180° diffusing lens available in:

**PC** white polycarbonate

Lens controls glare while hiding the LED's.

### Mounting:

Mounts directly on the surface

**FC** Fixed clips (set of 4)

**CS** Suspension cable  
2 meter length (set of 2)

### Application/Installation:

The **NTALB-T60/T100** LED bars be installed, for up or down applications or combined in multidirectional applications, even combining up-down lighting with different light ratios.

### Application/Installation:

Consult factory for damp application or splash area using our silicone jacketed IP67 sources. **(WP)**

### Voltage:

12 VDC  
24 VDC

### Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80).

All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.



### Homologation:

Conforms to ANSI/UL standard UL-2108  
Certified to CAN/CSA standard 22.2-9.0



## Ordering Matrix / Specification

Model	Bar	Length	Lens	Mounting	LED**	Color	Volts
<b>NTALB</b>	<b>T60</b> Ø60mm	1000 mm 2000 mm XX mm*	PC polycarbonate	<b>FC</b> Fixed Clips <b>CS</b> Suspension Cable *	UT30 UT30 WP UT60 UT60 WP UT120 UT120 WP UT120 RGB+WH	VWW (2400K) WW (2700,3000,3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
	<b>T100</b> Ø100mm						
					HP30 HP30WP HP120 HP120WP	VWW (2400K) WW (3000K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	
					UT39K CCT	(2700-6500K)****	
					RGB 150 RGB 150 WP	** Consult the LED linear source and driver data sheets for available wattages and characteristics.	
					RGB 300 RGB 300 WP	*** Consult Factory	
					RGB 600 RGB 600 WP	**** Color Correction	



### Natech Industrie

3154 boulevard Industriel, Laval, QC, H7L 4P7 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, info@natechlighting.com

This specification is valid as of 2019-01 and is subject to change without notice. Please confirm with the manufacturer before placing an order.  
Copyright 2014 Natech Industrie. All rights reserved.