

Project :	Date :
Cat No. :	Type :
Notes :	Volts :

Description:

The **NTALB-02SP** LED bar design provides a unique linear lighting solution combining style, performance and durability while reducing construction and operating costs through installation time, energy savings and a maintenance free application. Ideal for surface installations.

Housing:

The **NTALB-02SP** is a high precision extruded anodized aluminum bar that can accept a low-power LED source to medium power.

Lens:

Precision fit extruded acrylic for indoor use only available in:

FR Frosted

Mounting:

Mounts within on a surface with:

FC Fixed clips (set of 2)

Application/Installation:

The **NTALB-02SP** LED bar can be installed, for up, or down applications. This bar can be installed on surfaces, under cabinets.

Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80). All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optical dimmers and controls combination for your project.

Homologation:


Conforms to ANSI/UL standard UL-2108
Certified to CAN/CSA standard 22.2-9.0




NTALB-02SP - FR



NTALB-02SP - Endcaps



FC




MG

Ordering Matrix/Specification

Model	Bar	Lenght	Lens	Mount	LED**	Color	Volts
NTALB	02SP	1000mm 2000mm XX mm <small>Consult factory for special lenght</small>	FR Frosted OP Opalin	FC Fixed clip	UT30 UT30WP UT60 UT60WP UT120 UT120 RGB+WH	VWW (2400K) WW (2700,3000,3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
					HP30 HP30WP HP120 HP120WP HP147 HP147WP	VWW (2400K) WW (3000K) NW (4100K) WH (5000K) R (red) B (blue) V (green) A (amber)	
					UT39K CCT (White)	(2700-6500K)	
					RGB 150 RGB 150WP		
					RGB 300 RGB 300WP		
					RGB 600 RGB 600WP		

** Consult the LED linear source and driver data



Natech Industrie

3154 boulevard Industriel, Laval, QC, H7L 4P7 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, info@natechlighting.com

This specification is valid as of 2019-01 and is subject to change without notice. Please confirm with the manufacturer before placing an order. Copyright 2014 Natech Industrie. All rights reserved.