

Project :

Date :

Cat. No. :

Type :

Notes :

Volts :

Applications:

Ideal for areas where intelligent and RGB LED solutions are required.

- For decor, ambiance and public safety.
- Architectural accentuation with warm and cool white or ambiance creation with RGB versions.

Suitable for indoor architectural, hospitality, commercial and residential applications.

Look for other LEDIX IP56 rated products for outdoor applications.

Housing:

Stainless steel housing polished or painted aluminium precision fit parts and assembly.

Source:

- 0.56W Cool white 5900K 22 lumens
- 0.42W Warm white 3100K 14 lumens
- 0.28W In single color source
 - RED = 630nm
 - Green = 520nm
 - Blue = 459nm
- 0.84W For RGB

Finish:

Available in:

- Polished stainless steel finish
- Silver aluminium powder coated
- Graphite powder coated aluminium
- Old gold powder coated aluminium
- White
- Black

Options:

Choose one of the following

1. Standard (IP44)

Mounting:

Tera serie can be surface mount only.

Certification :

Conforms to ANSI/UL standard UL-2108
 Certified to CAN/CSA standard 22.2-9.0

Power supply requirements:



Requires a 12VDC output power supply and can also operate with a 14VDC source for automotive or RV applications.

Leads, connectors and power supply are supplied separately.

* RGB external controller needed sold separately.



03 Standard



Ordering Matrix / Specification

Model	Type	Installation	Voltage	Function(s)	Finish color	Color
NTWL	03		1 (12volts)			
	03= Tera	1- Surface		1- Standard	1- Aluminium 2- Stainless steel 3- Graphite 4- Old gold 5- White 6- Black	1- White 2- Warm white 3- Red 4- Green 5- Blue 6- RGB

