

# NTWL-04/05-XX-XXX

Project :	Date :			
Cat. No. :	Туре :			
Notes :	Volts :			

# Applications:

Ideal for areas where intelligent LED solutions are required.

- For decor, ambiance and public safety.
- Architectural accentuation with warm and cool white.

Suitable for indoor architectural, hospitality, commercial and residential applications.

Look for other LEDIX IP56 rated products for outdoor applications.

## Housing:

Stainless steel housing polished or painted aluminium precision fit parts and assembly.

#### Source:

- 0.56W Cool white 5900K 10 lumens
- 0.42W Warm white 3100K 7 lumens

# 0.28W In single color source

- RED = 630nm
  - Green = 520nm Blue = 459nm

# Finish:

- Available in:
- Polished stainless steel finish
- Silver aluminium powder coated
- Graphite powder coated aluminium
- Old gold powder coated aluminium
  - White
  - Black

# Options:

Choose one of the following 1. Standard (IP44)

## Mounting:

Standard Tico series can be surface mount only.

## **Certification :**

Conforms to ANSI/UL standard UL-2108 Certified to CAN/CSA standard 22.2-9.0

## Power supply requirements:

Requires a 12VDC output power supply and can also operate with a 14VDC source for automotive or RV applications.

Leads, connectors and power supply are supplied separately.



04 Standard



05 Standard



04 Standard

# **Ordering Matrix / Specification**

	Model	Туре	Installation	Voltage	Function(s)	_	Finish color	Color	04 Standard
	NTWL	-	-	<b>1</b> (12volts)		]-[			
_		04= Tico 05= Tico (with square plate)	1- Surface	]	1- Standard		1- Aluminium 2- Stainless steel 3- Graphite 4- Old gold 5- White 6- Black	1- White 2- Warm white 3- Red 4- Green 5- Blue	Intertek 4010322

#### **Natech Industrie**

1995 Francis Hughes, Laval, Qc, H7S 2G2: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com