

| | |
|------------|---------|
| Project : | Date : |
| Cat. No. : | Type : |
| Notes : | Volts : |


9 Watts LED retrofit dimmable and compatible with can 3" and 4" for a general effective lighting in dry and wet places.
Option installation for insulated ceiling (1)

| | |
|-----------------------------|---|
| Application: | For cans 3 or 4 inches |
| Light color: | 3000K warm white 650lm |
| Fixture finish: | Surface in white, electrostatic powder coated |
| Fixture material: | Aluminum and PVC lens |
| Diffuser: | Acrylic lens |
| Optic: | 85° |
| Voltage: | 120 VAC dimmable* |
| Lamp life: | >40,000 hours L ₇₀ Energy Star |
| Maximum wattage: | 9 Watts |
| Fixation: | KIC: can 3" for model NTTP120-RT3 can 4" for model NTTP120-RT4 PF: Plaster frame for new construction adaptors GU10 or E26 |
| Working temperature: | -30°C+50°C |
| PF: | >0.9 |
| CRI: | >80 |


* must used a recommended dimmer





NTTP120RT-3-WW



NTTP120RT-4-WW



(1) LED Retrofit kit with certified can for insulated ceiling installation.



Ordering Matrix / Specification

| Model | Type | Color | Option | Option | Option |
|-----------|------------------------------|-------|-------------|----------------------------------|--|
| NTTP120RT | | WW | | | |
| | 3 for 3" can 4 for 4" can | | GU10 E26 | KIC Can for insulated ceiling | PF Plaster frame for new construction |