

Project :

Date :

Cat. No. :

Type :

Notes :

Volts :

The NTWL-RD/SQ-1W recessed wall series are available round or square 1W LED sources, suitable for all residential and commercial installations. Applications for a range from cabinet, millwork, closet, corridor to stairs.

Application:	Stairs, furniture, cabinet, corridor	
Light color:	5000K white	95lm
	4100K natural white	90lm
	3000K warm white	85lm
Fixture finish:	Anodized aluminum	
Fixture material:	Aluminium	
Optic:	45° model NTWL-RD/SQ-1W-45-XX	
	120° model NTWL-RD/SQ-1W-120-XX	
Voltage:	350 MA	
Lamp life:	50,000 hours	
Maximum wattage:	1.245 Watt	
Fixation:	Spring clips	
Working temperature:	-30 - +55°C	
Certification:	Conform to ANSI/UL standard 2108	
	Certified to CAN/CSA standard 22.2-9.0	
Driver constant current class II recommended:		
NTLD3W-350MA-12	source 12V	1 to 3 units
NTLD350MA	for 120VAC	1 to 6 units
NTLD350MA-WP	for 120VAC	1 to 6 units


* For dimming or control option, please consult factory

Ordering Matrix / Specification


Model	Type	Wattage	Beam	Color
NTWL		1W		
	RD (round)		45 (45 degrees)	WH (white)
	SQ (square)		120 (120 degrees)	NW (natural white)
				WW (warm white)





NTWL-RD-1W-45-XX




NTWL-SQ-1W-45-XX



NTWL-RD-1W-120-XX



NTWL-SQ-1W-120-XX



Natech Industrie

1995 Francis Hughes, Laval, Qc H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-10 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.