

NT-OTM-SS100-12 OR 24

Power supply ultra thin 100 watts 12V or 24V

Project:	Date :
Cat. No.:	Type :
Notes:	Volts :

This power supply is a constant voltage for indoor or outdoor applications, non dimmable.


100% full load burn-in test

Protection: Over load/over voltage/short circuit

Low temperature resistant (-45°C)

This driver should be installed by qualified and professional person.





Specifications

Product name	AC to DC Switching 12V 24V 100w slim led driver
Output power	100W
AC input voltage rage	85-264V
output frenquency	50-60Hz
Efficiency	>85%
Output voltage	12V/24V±5%
Output current	8.3A/4.17A
Protection	Over Load, Over Voltage
Application	LED Lighting, monitor equipment
Туре	Constant Voltage
Protected level	IP67
Material	Aluminium, Copper
	I/P-O/P: 1.5KvAC 1 minute
Withstand voltage	I/P-FG: 1.5KvAC 1 minute
	O/P-FG: 0.5KvAC 1 minute
Working temperature	-40°C~+80°C
Working Humidity	20%~90%RH
Size	182*62*18.6mm
Weight	0.46kg

Natech Industrie

1995 Francis Hughes, Laval, QC, H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com