

Project :

Date :

Cat. No.:

Type :

Notes :

Volts :

Applications:

The NTTLC-180W-R/G/B/WH is powered by 2 X 27 LED CREE chips total 18R, 12G, 12B and 12 WH (5000K). Materials and construction ensures LED longevity while providing maximum lighting from 10 to 15 meters

Designed for high efficiency and long life suitable for a myriad of innovative architectural and site lighting solutions.

- Architectural, building and facade,
- Column
- Fountains statues, landscape and other elements,

Housing:

Cast-aluminium IP66 black housing ensure 100% heat dissipation since LED is mounted directly on the body allowing full functionality and lighting flux performance. The 2 blocks of 27 LEDs can be adjusted independently to allow more uniform lighting over a long distance. Stainless steel hardware.

Lenses and optical cells/ CRI

Tempered glass, with perimeter gasket pressure points. Optical assembly is hermetically sealed providing ingress protection. Standard CRI 80 and standard Spot 3 or 10 degrees

Finish:

Corrosion and salt spray resistant electrostatic applied polyester powder coat finish black standard.

Voltage (50/60 Hz)

2 24 Volts DC not included

Caractéristiques:




- Protocol DMX 512 signal 4 channels
- Can set the address via an encoder (not included see factory)
- 80,000 hours
- Weight: 9.7kg (20 lbs),
- Working temperature:
Min -30°C (-22°F)
Max +55°C (+131°F)
- Standard with 2 x 0.7m waterproof 5-pin connector
- Lumens: 40 lumens/watt total

Mounting:


Standard yoke mount with double adjustment

Certification :

Meets and exceeds industry ANSI/UL UL-1598, 8750, CAN/CSA, CSA-22.2 no 250.0 & CSA-22.2 no 250.13 standards for safety and compliance.



Accessories



TG-EXT cable


Extension cable 10 feet 5 pins



TG-TT cable

T cable 28cm each side 5 pins

Yoke details:



Red:	1314 lumens	634nm
Green:	1716 lumens	521nm
Blue	492 lumens	465nm
White	2040 lumens	5000K

Ordering Matrix / Specification

Model	Wattage	Voltage	Color	Lens	Beam	Mounting	Housing
NTTLC	180W	2 24 Volts	R/G/B/WH	C clear	S3 3 degree S10 10 degree	V Y Yoke	B B black
					DMX		

Natech Industrie

1995 Francis Hughes, Laval, QC, H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-10 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.