

Project :	Date :
Cat. No :	Type :
Notes :	Volts :

### Description:

The **NTALB-49R** LED bar design provides a unique linear lighting solution combining style, performance and durability in a medium width strip, while reducing constructions and operating costs through installation time, energy savings and maintenance free application.

### Housing:

The **NTALB-49R** is a high precision extruded anodized aluminum that can accept a LED linear source from normal to high power. Each assembled Led Bar included two (2) aluminum end caps screwed.

### Lens:

Precision fit extruded acrylic snap-in lens available in:

- OP** Opal (white)
- FR** Frost

### Mounting:

- Mounts directly on surface
- FC** Fixed clips (set of 2)

### Application/Installation:

The **NTALB-49R** LED bar can be installed for up and down light diffusion directly on wall with 2 clips. Consult factory for damp application or splash area using our silicone jacketed IP67 sources. **(WP)**

### Voltage:

- 12 VDC
- 24 VDC

### Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80).

All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.


### Homologation:

#### MODEL NTALB


Conforms to ANSI/UL standard UL-2108  
Certified to CAN/CSA standard 22.2-9.0

#### MODEL NTALBH

Conforms to ANSI/UL standard UL-1598  
Certified to CAN/CSA standard 22.2-250.0




NTALB-49R



## Ordering Matrix / Specification

Model	Bar	Length	Lens	Mounting	LED**	Color	Volts
NTALB*	49R						
NTALBH**		1000 mm 2000 mm XX mm*	FR Frosted OP Opal	FC Fixed Clips	UT30 UT30 WP UT60 UT60 WP UT120 UT120 WP UT120 RGB+WH	VWW (2400K) WW (2700,3000,3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
					HP30 HP30WP HP120 HP120WP	VWW (2400K) WW (3000K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	
					UT39K CCT (White)	(2700-6500K)****	
					RGB 150 RGB 150 WP		** Consult the LED linear source and driver data sheets for available wattages and characteristics.
					RGB 300 RGB 300 WP		*** Consult Factory **** Color Correction



Remote driver available

### Natech Industrie

1995 Francis Hughes, Laval H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-09 and is subject to change without notice. Please confirm with the manufacturer before placing an order.  
Copyright 2014 Natech Industrie. All rights reserved.