

Project :	Date :
Cat. No :	Type :
Notes :	Volts :

Description:

The **NTALB-44** LED bar design provides a unique linear lighting solution combining style, performance and durability while reducing constructions and operating costs through installation time, energy savings and maintenance free application.

Housing:

The **NTALB-44** is a high precision extruded anodized aluminum that can accept a LED linear source from normal to high power.

Lens:

Precision fit extruded polycarbonate snap-in 180° diffusing lens available in:

OP Opal (white)

BK Black PC

Lens controls glare while hiding the LED's.

Mounting:

Mounts directly on the surface

FC Fixed clips (set of 2)

CS Suspension cable)

2 meters length (set of 2)

Application/Installation:

The **NTALB-44** LED bar be installed, for up or down applications or combined in multidirectional applications, even combining up-down lighting with different light ratios.

Application/Installation:

Consult factory for damp application or splash area using our silicone jacketed IP67 sources. **(WP)**

Voltage:

12 VDC

24 VDC

Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80).


All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.

Homologation:

Conforms to ANSI/UL standard UL-2108


Certified to CAN/CSA standard 22.2-9.0



NTALB-44- OP



NTALB-44- end caps



NTALB-44BK

Ordering Matrix / Specification

Model	Bar	Length	Lens	Mounting	LED**	Color	Volts
NTALB	44 44 (aluminium) 44BK (black)	1000 mm 2000 mm XX mm*	OP Opalin BK Black PC	FC Fixed Clips CS Suspension Cable *	UT30 UT30 WP UT60 UT60 WP UT120 UT120 WP UT120 RGB+WH	VWW (2400K) WW (2700,3000,3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
					UT39K CCT (White)	(2700-6500K)****	
					RGB 150 RGB 150 WP		
					RGB 300 RGB 300 WP		

* Consult factory for special lengths.

** 2 meters standard Consult factory for special length

** Consult the LED linear source and driver data sheets for available wattages and characteristics.

*** Consult Factory

**** Color Correction

