

Project :	Date :
Cat. No. :	Type :
Notes :	Volts :

Applications:

Ideal for areas where intelligent and RGB LED solutions are required.

- For decor, ambiance and public safety.
- Architectural accentuation with warm and cool white or ambiance creation with RGB versions..

Suitable for indoor architectural, hospitality, commercial and residential applications.

Look for other LEDIX IP56 rated products for outdoor applications.

Housing:

Stainless steel housing polished or painted aluminium precision fit parts and assembly.

Source:

0.56W	Cool white 5900K 23 lumens
0.42W	Warm white 3100K 15 lumens
0.28W	In single color source
	RED = 630nm
	Green = 520nm
	Blue = 459nm
0.84W	For RGB

Finish:

Available in:

- Polished stainless steel finish
- Silver aluminium powder coated
- Graphite powder coated aluminium
- Old gold powder coated aluminium
- White
- Black

Options:

Choose one of the following:

1. Standard (IP44)

Mounting:

Standard Sona 12 can be only surface mount and 13, 14 can be only semi recessed with clips.

Certification :

Conforms to ANSI/UL standard UL-2108
Certified to CAN/CSA standard 22.2-9.0

Power supply requirements:


Requires a 12VDC output power supply and can also operate with a 14VDC source for automotive or RV applications.

Leads, connectors and power supply are supplied separately.



- * RGB external controller needed sold separately.





12 Standard



13 Standard



2. semi recessed with clips



2. semi recessed with clips

Ordering Matrix / Specification

Model	Type	Installation	Voltage	Function(s)	Finish color	Color
NTWL			1 (12volts)			
	12= Sona	1- Surface		1- Standard	1- Aluminium	1- White
	13= Sona (with round plate)	2- Semi-recessed			2- Stainless steel	2- Warm white
	14= Sona (with square plate)				3- Graphite	3- Red
					5- White	4- Green
					6- Black	5- Blue
						6- RGB



Natech Industrie

1995 Francis Hughes, Laval, Qc, H7S 2G2: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-09 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.