

Project :	Date :
Cat. No :	Type :
Notes :	Volts :

Description:

The **NTALB-44** LED bar design provides a unique linear lighting solution combining style, performance and durability while reducing constructions and operating costs through installation time, energy savings and maintenance free application.

Housing:

The **NTALB-44** is a high precision extruded anodized aluminum that can accept a LED linear source from normal to high power.

Lens:

Precision fit extruded polycarbonate snap-in 180° diffusing lens available in:

OP Opal (white)

BK Black PC

Lens controls glare while hiding the LED's.

Mounting:

Mounts directly on the surface

FC Fixed clips (set of 2)

CS Suspension cable)
2 meters length (set of 2)

Application/Installation:

Consult factory for damp application or splash area using our silicone jacketed IP67 sources. **(WP)**

Voltage:

12 VDC

24 VDC

Electrical and Electronics:

High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80).


All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.

Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.

Homologation:

Conforms to ANSI/UL standard UL-2108


Certified to CAN/CSA standard 22.2-9.0



NTALB-44- OP




NTALB-44- end caps



NTALB-44BK

Ordering Matrix / Specification

Model	Bar	Length	Lens	Mounting	LED**	Color	Volts
NTALB	44						
	44 (aluminium) 44BK (black)	1000 mm 2000 mm XX mm*	OP Opalin BK Black PC	FC Fixed Clips CS Suspension Cable *	UT30 (14.8W/M 450LM) UT30 WP UT60 (10W/M 880LM) UT60 WP UT120 (20W/M 1790LM) UT120 WP UT120 RGB+WH (19.2W/M)	VWW (2400K) WW (2700, 3000, 3500K) NW (4100K) WH (5000K) R (Red)*** B (Blue)*** G (Green)*** A (Amber)***	12VDC 24VDC
		* Consult factory for special lengths.		* 2 meters standard Consult factory for special length	HP30 (14.5W/M 1279LM) HP30WP HP60 (10W/M 1070LM) HP7.2 (7.2W/M 1009LM) HP10 (10W/M 1450LM) HP120 (19.2W/M 1600LM) HP120WP VHP64 (22W/M 3437LM) VHP64WP CCT HP304 (8.4W/M 560-700LM) UT39K (20W/M 710-830LM) UT39K WP RGB 150 (7.2W/M) RGB 150 WP RGB 300 (14.4W/M) RGB 300 WP RGB 840 (14.4W/M) RGBW192 (15.3W/M 343LM) RGBW192 WP RGB 860 (16W/M 320LM)	WW (3000K) NW (4100K) WH (5000K) WW (3000K) NW (4100K) WH (5000K) (2700-6500K)****	24VDC



** Consult the LED linear source and driver data sheets for available wattages and characteristics
*** Consult Factory
**** Color Correction

Natech Industrie

1995 Francis Hughes, Laval H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, www.natechlighting.com, service@natechlighting.com

This specification is valid as of 2022-09 and is subject to change without notice. Please confirm with the manufacturer before placing an order.
Copyright 2014 Natech Industrie. All rights reserved.