

|           |         |
|-----------|---------|
| Project : | Date :  |
| Cat No. : | Type :  |
| Notes :   | Volts : |

### Description:

The **NTALB-17** LED bar design provides a unique linear lighting solution combining style, performance and durability in a medium width strip, while reducing constructions and operating costs through installation time, energy savings and maintenance free application.

### Housing:

The **NTALB-17** is a high precision extruded anodized aluminum that can accept a LED linear source from normal to high power.

### Lens:

Extruded acrylic lens setting by pressure on the aluminum profile.

**FR** Frosted  
**OP** Opal (white)  
**BK** Black PC

### Mounting:

Mounts within a recess section with clips.

**FC** Fixed clips (set of 2)  
**SC** Swivel metal clips (set of 2)

### Application/Installation:

The **NTALB-17** LED bar can be installed for up, or down applications or side for 180° light diffusion. Consult factory for damp application or splash area using our silicone jacketed IP67 sources. **(WP)**

### Voltage:

12 VDC  
24 VDC

### Electrical and Electronics:


High quality diodes tested (LM80) and certified life cycle for 60,000 hours (L80).

All certified electrical and electronic components have been re-tested over the years for compatibility within products and for specific applications. All products exceed current standards.


Power supply not included, consult factory. Consult the LED specification sheet for the appropriate optional dimmers and controls combination for your project.

### Homologation:

Conforms to ANSI/UL standard UL-2108  
Certified to CAN/CSA standard 22.2-9.0




NTALB-17



NTALB-17R5



### Accessories



NTALU17-B-L



NTALU17-B-T



NTALU17-B-X




Mounting clip



Spring clip



NTALB-17R5-BK




ENDCAPS


### Ordering Matrix / Specification

| Model        | Bar                                    | Length                       | Lens                                 | Mounting                                  | LED**                                                                   | Color                                                                                                                        | Volts          |
|--------------|----------------------------------------|------------------------------|--------------------------------------|-------------------------------------------|-------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>NTALB</b> |                                        |                              |                                      |                                           |                                                                         |                                                                                                                              |                |
|              | NTALB-17<br>NTALB-17R5<br>NTALB-17R5BK | 1000 mm<br>2000 mm<br>XX mm* | FR Frosted<br>OP Opal<br>BK Black PC | FC Fixed clips<br>FCS Special fixed clips | UT30<br>UT30 WP<br>UT60<br>UT60 WP<br>UT120<br>UT120 WP<br>UT120 RGB+WH | VWW (2400K)<br>WW (2700,3000,3500K)<br>NW (4100K)<br>WH (5000K)<br>R (Red)***<br>B (Blue)***<br>G (Green)***<br>A (Amber)*** | 12VDC<br>24VDC |

\* Consult factory for special lengths.



NTALB-17



NTALB-17R5

HP30 (14.5W/M 1279LM)  
HP30WP  
HP60 (10W/M 1070LM)

HP7.2 (7.2W/M 1008LM)  
HP10 (10W/M 1450LM)  
HP120 (19.2W/M 1600LM)  
HP120WP  
VHP64 (22W/M 3437LM)  
VHP64WP

CCT  
HP304 (14W/M 560-700LM)  
UT39K (12W/M 750-830LM)  
UT39K WP

RGB 150 (7.2W/M)  
RGB 150 WP

RGB 300 (14.4W/M)  
RGB 300 WP  
RGB 840 (14.4W/M)

RGBW192 (15.3W/M 343LM)  
RGBW192 WP  
RGBW 896 16W/M 320LM)

WW (3000K)  
NW (4100K)  
WH (5000K)

WW (3000K)  
NW (4100K)  
WH (5000K)

(2700-6500K)\*\*\*

\*\* Consult the LED linear source and driver data sheets for available wattages and characteristics  
\*\*\* Consult Factory  
\*\*\*\* Color Correction

### Natech Industrie

1995 Francis Hughes, Laval H7S 2G2 T: (450) 629-1169, F: (450) 629-1168, [www.natechlighting.com](http://www.natechlighting.com), [service@natechlighting.com](mailto:service@natechlighting.com)

This specification is valid as of 2022-09 and is subject to change without notice. Please confirm with the manufacturer before placing an order.  
Copyright 2014 Natech Industrie. All rights reserved.